



Advanced Flagpole Products & Services

Phone: 919-304-0009
 Fax: 413-803-4496
 Toll-Free: 877-461-6719

Banner-Arm Flagpole Specification Sheet

Model	Exposed height	Butt diameter	Top diameter	Unflagged Constant Wind Speed	Flagged Constant Wind Speed		Weight
B20	20'	4 ^{3/16"}	2 ^{3/4"}	180 ^{MPH}	10' x 4'	131 ^{MPH}	22 ^{LBS}
B25	25'	4 ^{1/2"}	2 ^{3/4"}	162 ^{MPH}	10' x 4'	130 ^{MPH}	33 ^{LBS}
B25-IHL	25'	4 ^{1/2"}	2 ^{3/4"}	174 ^{MPH}	10' x 4'	137 ^{MPH}	41 ^{LBS}
B30	30'	4 ^{14/16"}	2 ^{3/4"}	130 ^{MPH}	15' x 4'	93 ^{MPH}	44 ^{LBS}
B30	30'	4 ^{14/16"}	2 ^{3/4"}	130 ^{MPH}	15' x 5'	90 ^{MPH}	44 ^{LBS}
B30-IHL	30'	4 ^{14/16"}	2 ^{3/4"}	162 ^{MPH}	15' x 4'	118 ^{MPH}	56 ^{LBS}
B30-IHL	30'	4 ^{14/16"}	2 ^{3/4"}	162 ^{MPH}	15' x 5'	115 ^{MPH}	56 ^{LBS}
B35	35'	5 ^{1/4"}	2 ^{3/4"}	118 ^{MPH}	17' x 4'	87 ^{MPH}	61 ^{LBS}
B35	35'	5 ^{1/4"}	2 ^{3/4"}	118 ^{MPH}	17' x 5'	84 ^{MPH}	61 ^{LBS}
B35-IHL	35'	5 ^{1/4"}	2 ^{3/4"}	155 ^{MPH}	17' x 4'	112 ^{MPH}	76 ^{LBS}
B35-IHL	35'	5 ^{1/4"}	2 ^{3/4"}	155 ^{MPH}	17' x 5'	109 ^{MPH}	76 ^{LBS}
B40	40'	5 ^{2/3"}	2 ^{3/4"}	115 ^{MPH}	20' x 5'	78 ^{MPH}	80 ^{LBS}
B40-IHL	40'	5 ^{2/3"}	2 ^{3/4"}	155 ^{MPH}	20' x 5'	109 ^{MPH}	98 ^{LBS}

Note: All flagpoles are available using either a sleeve base or a tilting base.

- «T» stands for Traditional type
- «IH» stands for Internal Halyard / Small access door
- «IHL» stands for Internal Halyard / Large access door